



Wing Top Batch Pasteurizer

Capacity: 800 Gallons/3028 Liters with 20% Head Space

Power: SEW-Eurodrive 1.5 HP Gearmotor, Single or Three Phase

Agitation: Standard Blade Bottom Agitation

Heating: Min. 1,200,000 BTU Hot Water or Steam Boiler Sold Separately

Jacket: Dimple Plate, Bottom & Side Zone, Max. 70 PSI, Max. 50 GPM

Ports: (2) 1.5" TC Ports or (2) Thermowells for the Product and Indicating

Thermometer, (1) 1.5" Airspace TC Port, (2) 1.5" TC CIP Sprayballs Ports, (1) 3" TC Airspace Element Port, (1) TC Milk Inlet Port, and (2)

Lifting Lugs

Lid: Flat Top with Center Bridge. The (2) Hinge Lids are Removable

Bottom: Slight Pitch Toward Outlet

Insulation: Polyurethane

Walls: 304 Stainless Steel, No. 4 Finish (316 SS Available)

Legs: (4) Stainless Legs with Adjustable Ball Feet

Outlet: 2" Leak Detect Valve Ready

Dimensions: TBD

Pasteurizer with Agitation:	\$ 32,000.00
Additional Pasteurizing Accessories:	
Anderson-Negele Chart Recorder, Product & Airspace Probe	\$ 3,500.00
Leak Detection Valve, Gasket, and Food Grade Lubricant	\$ 1,800.00
Airspace Heater 3,000 Watt, Single Phase, 15 Amp Element & NEMA 4 Rheostat Controller	\$ 2,200.00
BATCH PASTEURIZER WITH FULL PMO ACCESSORIES	\$ 39,500.00
Add-On Features :	
316 Stainless Steel Interior-Extra Corrosion Protection for Product Contact Surface Area	\$ 3,800.00
Cone or Dish Bottom Tank Design - no additional charge	\$ -
Side and Bottom Scrape Agitation	\$ 2,700.00
	\$ 2,500.00