



Conical/Dome Top Batch Pasteurizer



Capacity: 200 Gallons/757 Liters with 20% Head Space

Power: SEW-Eurodrive .75 HP Gearmotor, Single or Three Phase

Agitation: Standard Bottom Blade & Small Airspace Blade Agitation

Heating: Min. 350,000 BTU Hot Water or Steam Boiler is Required

Jacket: Dimple Plate, Single Zone, Max. 70 PSI, Max. 50 GPM

Ports: (2) 1.5" TC Ports or (2) Thermowells for the Product and Indicating Thermometer, (1) 1.5" Airspace TC Port, (2) 1.5" TC CIP Sprayballs Ports, (1) 3" TC Airspace Element Port, (1) TC Milk Inlet Port, (1) Air Vent and (2) Lifting Lugs

Lid: 17" Manway Cover

Bottom: Slight Pitch Toward Outlet


Insulation: Polyurethane

Walls: 304 Stainless Steel, No. 4 Finish (316 SS Available)

Legs: (4) Stainless Legs with Adjustable Ball Feet (Casters Available)

Outlet: 2" Leak Detect Valve Ready

Dimensions: TBD



Pasteurizer with Agitation:

\$ 18,000.00

Add-Pasteurizing Accessories:

Anderson-Negele Chart Recorder, Product & Airspace Probe	\$ 3,500.00
Leak Detection Valve, Gasket, and Food Grade Lubricant	\$ 1,800.00
Airspace Heater 1,250 Watt, Single Phase, 10 Amp Element & NEMA 4 Rheostat Controller	\$ 1,600.00

BATCH PASTEURIZER WITH FULL PMO ACCESSORIES

\$ 24,900.00

